



## Castrol Classic XL 30

Oil for Classic Vehicles

### Description

Castrol Classic XL 30 is a high quality monograde engine oil which is also used in a number of manually operated gearboxes, including Wilson pre-selects, fitted to vintage and classic cars.

Castrol Classic XL 30 contains selected additives to control high temperature "varnish", give good anti-wear performance and help prevent the build up of low temperature "sludge".

### Application

Castrol XL 30 is suitable for use in automotive gasoline engines where an API SB performance level is recommended.

### Advantages

Castrol Classic XL 30 is formulated for:

#### Cars

- Summer use in petrol engines
- Winter use in engines which would otherwise have high oil consumption
- Some manually operated gearboxes

#### Motor Cycles

- Summer use in twin-cylinder 4-stroke engines
- Certain motorcycle gearboxes

## Typical Characteristics

| Name                      | Method     | Units              | Castrol Classic XL 30 |
|---------------------------|------------|--------------------|-----------------------|
| Density @ 15C, Relative   | ASTM D4052 | g/ml               | 0.888                 |
| Viscosity, Kinematic 100C | ASTM D445  | mm <sup>2</sup> /s | 11.1                  |
| Viscosity, Kinematic 40C  | ASTM D445  | mm <sup>2</sup> /s | 99                    |
| Viscosity Index           | ASTM D2270 | None               | 97                    |
| Pour Point                | ASTM D97   | °C                 | -21                   |
| Flash Point, PMCC         | ASTM D93   | °C                 | 226                   |
| SAE Viscosity Grade       | J300       |                    | 30                    |

## Product Performance Claims

API SB

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Classic XL 30

17 Dec 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)