



Classic D 140

Gear Oil for Classic Vehicles

Description

Classic D 140 is a high viscosity gear oil formulated with high quality mineral oils. It is fortified with an anti-oxidation and anti-wear additive to ensure that the oil is able to withstand the oxidising conditions which are present in gearboxes/ axles during service and to ensure that the gear teeth are protected against wear.

Application

Classic D 140 is suitable for the lubrication of most types of gears including helical, spur, bevel and worm; but must not be used for hypoid gears where API GL-4 or GL-5 oils are recommended. The high viscosity and type of additive system make it particularly suitable for use in older vehicles where some wear with age may have occurred or where the lubricated application may contain sensitive metal (yellow) components (eg. brass/bronze).

Typical Characteristics

Name	Method	Units	Classic D 140
Density @ 15C, Relative	ASTM D4052	g/ml	0.905
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	30.6
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	472
Viscosity Index	ASTM D2270	None	94
Pour Point	DIN-ISO 3016	°C	-9
Flash Point, COC	ASTM D92	°C	272

Product Performance Claims

API GL-3

Classic D 140
15 Jan 2016
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com