



GTX Classic 10W/40

Oil for classic vehicles

Description

Castrol GTX Classic 10W/40 is a multigrade engine oil of good all-round performance, formulated with high-quality mineral oils plus selected additives, ideally suited to older technology engines and classic cars.

Designed to meet the vehicle manufacturers' original engine oil requirements for older vehicles running under normal operational and service conditions.

Contains anti-wear additives to provide the levels of protection necessary for older technology engines.

Recommended for vehicles manufactured post-1978 to pre-1993.

Application

Castrol GTX Classic 10W/40 is suitable for use in vehicles where the manufacturer recommended an API SG or earlier specification 10W-40 engine oil.

Typical Characteristics

Name	Method	Units	Castrol GTX Classic 10W/40
Density @ 15C, Relative	ASTM D4052	g/ml	0.869
Viscosity, Kinematic 100C	ASTM D7042	mm ² /s	13.6
Viscosity, Kinematic 40C	ASTM D7042	mm ² /s	94
Viscosity Index	ASTM D2270	None	147
Viscosity, CCS -25C	ASTM D5293	mPa.s (cP)	6576
Pour Point	ASTM D97	°C	-33
Flash Point, COC	ASTM D92	°C	236
Ash, Sulphated	ASTM D874	% wt	1.0

Product Performance Claims

API SG

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

GTX Classic 10W/40

04 Apr 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com